

U.S. DEPARTMENT OF LABOR
Occupational Safety and Health Administration

Form Approved
OMB No. 44-R1387

MATERIAL SAFETY DATA SHEET

Required under USDL Safety and Health Regulations for Ship Repairing,
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

SECTION I

MANUFACTURER'S NAME Dexter Corporation, Hysol Division		EMERGENCY TELEPHONE NO. 415/687-4201
ADDRESS (Number, Street, City, State, and ZIP Code) 2850 Willow Pass Road (P.O. Box 312), Pittsburg, California 94565		
CHEMICAL NAME AND SYNONYMS		TRADE NAME AND SYNONYMS EA 911F Part B
CHEMICAL FAMILY Mercaptan	FORMULA	

SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS			BASE METAL		
CATALYST			ALLOYS		
VEHICLE Mercaptan	88		METALLIC COATINGS		
SOLVENTS			FILLER METAL PLUS COATING OR CORE FLUX		
ADDITIVES Aliphatic Amine	2		OTHERS		
OTHERS Asbestos*	10				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
*If it is necessary to sand the cured adhesive "wet sanding" is					
recommended to eliminate airborne asbestos. For "dry sanding" follow					
recommendations in Section VIII.					

SECTION III - PHYSICAL DATA

BOILING POINT (°F.) Decompose before boiling	SPECIFIC GRAVITY (H ₂ O=1)	1.25
VAPOR PRESSURE (mm Hg.) N/A	PERCENT VOLATILE BY VOLUME (%)	Unknown
VAPOR DENSITY (AIR=1) N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER		
APPEARANCE AND ODOR Viscous grey paste with sulphur-like odor		

SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used) >200°F TCC	FLAMMABLE LIMITS	LeI	UeI
EXTINGUISHING MEDIA Chemical foam, CO ₂ , dry chemicals			
SPECIAL FIRE FIGHTING PROCEDURES None			
UNUSUAL FIRE AND EXPLOSION HAZARDS None			